

48.3mm Galvanised Scaffold Tube With Yield Strength 245N/Mm2 And Tensile Strength 420N/Mm2

Our Product Introduction

for more products please visit us on bythaiscaff.com

Basic Information

- Place of Origin: China
- Brand Name: Bythai Scaffolding
- Certification: SGS
- Model Number: BT01
- Price: \$5-\$18
- Packaging Details: In bundles
- Delivery Time: 7-15 days
- Payment Terms: TT/LC
- Supply Ability: 1000tons per month




Product Specification

- Standard: EN39
- Weight: 6.4kg/m
- Tensile Strength: 420N/mm2
- Diameter: 48.3mm
- Thickness: 3.2mm
- Application: Scaffolding
- Yield Strength: 245N/mm2
- Surface Treatment: Galvanised
- Highlight: **48.3mm Galvanised Scaffold Tube, 245N/Mm2 Galvanised Scaffold Tube, 420N/Mm2 Galvanised Scaffolding Tube**



More Images



48.3mm Galvanised Scaffold Tube With Yield Strength 245N/Mm2 And Tensile Strength 420N/Mm2

Product Description:

Galvanised Scaffold Tube

The Galvanised Scaffold Tube is a high-quality and versatile building material that is essential for any scaffolding project. Made from hot dip galvanized scaffolding steel, it is known for its exceptional strength, durability, and corrosion resistance.

Product Overview

The Galvanised Scaffold Tube is a hollow cylindrical pipe that is used to create scaffolding structures. It is available in various sizes and lengths to suit different construction needs. The tube has a yield strength of 245N/mm² and a tensile strength of 420N/mm², making it one of the strongest and most reliable scaffolding materials on the market.

Application

Scaffolding is an essential part of any building construction, repair, or maintenance project. The Galvanised Scaffold Tube is specifically designed for scaffolding applications and is ideal for supporting workers and materials at elevated heights. It is widely used in both commercial and residential construction projects.

Surface Treatment

The Galvanised Scaffold Tube undergoes a hot-dip galvanizing process, where it is coated with a layer of zinc to protect it from corrosion. This surface treatment not only enhances its appearance but also provides long-lasting protection against rust and other environmental factors.

Key Features

Corrosion Resistance: The hot dip galvanizing process ensures that the scaffold tube is highly resistant to corrosion, making it suitable for use in all weather conditions.

High Strength: With a yield strength of 245N/mm² and a tensile strength of 420N/mm², the Galvanised Scaffold Tube can withstand heavy loads and provide a stable platform for workers.

Durable: The zinc coating and high-quality steel make the scaffold tube extremely durable, ensuring it has a long lifespan even in harsh environments.

Lightweight: Despite its strength, the scaffold tube is lightweight, making it easy to transport and assemble on site.

Easy to Assemble: The scaffold tube is designed for easy assembly, saving time and labor costs on construction sites.

Cost-Effective: The Galvanised Scaffold Tube is a cost-effective solution for scaffolding needs, as it requires minimal maintenance and has a long lifespan.

Conclusion

The Galvanised Scaffold Tube is an essential component of any scaffolding system. With its high strength, durability, corrosion resistance, and other key features, it is the preferred choice for builders, contractors, and construction companies. It provides a safe, stable, and cost-effective solution for all scaffolding needs.

Features:

Product Name: Galvanised Scaffold Tube

Weight: 6.4kg/m

Yield Strength: 245N/mm²

Standard: EN39

Surface Treatment: Galvanised

Scaffold Tube Caps

Q195 Scaffolding Tubes and Pipes

Galvanized Scaffolding Pipe Tube

Scaffolding Steel Tube

Technical Parameters:

| Attribute | Value |
|-------------------|--------------------------|
| Name | Galvanised Scaffold Tube |
| Weight | 6.4kg/m |
| Tensile Strength | 420N/mm ² |
| Yield Strength | 245N/mm ² |
| Material | Galvanised Steel |
| Standard | EN39 |
| Surface Treatment | Galvanised |

| | |
|-------------|-------------|
| Application | Scaffolding |
| Thickness | 3.2mm |
| Diameter | 48.3mm |

Applications:

Galvanised Scaffold Tube

Brand Name: Bythai Scaffolding

Model Number: BT01

Place of Origin: China

Certification: SGS

Are you in need of high-quality scaffolding materials? Look no further than Bythai Scaffolding's Galvanised Scaffold Tube.

Made in China and certified by SGS, our scaffolding steel tube is the perfect solution for all your scaffolding needs. Our hot dip galvanized scaffolding steel tube is stamped with the Bythai Scaffolding logo, ensuring its authenticity and superior quality.

With a diameter of 48.3mm and a thickness of 3.2mm, our galvanised scaffold pole offers excellent strength and durability. It has a yield strength of 245N/mm², making it suitable for heavy-duty construction projects.

Our galvanised scaffold tube is not only strong, but it is also corrosion-resistant. The hot dip galvanizing process ensures that the tube is coated with a layer of zinc, protecting it from rust and other forms of damage. This makes it suitable for use in both indoor and outdoor construction projects.

One of the most significant advantages of our galvanised scaffold tube is its versatility. It is commonly used in various scaffolding applications, including building construction, renovation, and maintenance. Its sturdy structure and reliable performance make it a preferred choice among contractors and construction workers.

At Bythai Scaffolding, we understand the importance of timely delivery in the construction industry. That's why we offer a fast turnaround time of 7-15 days for all orders. We also provide flexible payment options, including TT and LC, to make the purchasing process convenient for our clients.

Our galvanised scaffold tube is priced competitively, starting from \$5 and going up to \$18, depending on the quantity ordered. We package our tubes in bundles to ensure safe transportation and easy handling on the job site. With a supply ability of 1000 tons per month, we can cater to both small and large orders efficiently.

So why wait? Choose Bythai Scaffolding's Galvanised Scaffold Tube for all your scaffolding needs and experience the difference in quality and performance. Contact us today to place your order!

Thickness: 3.2mm

Diameter: 48.3mm

Surface Treatment: Galvanised

Application: Scaffolding

Yield Strength: 245N/mm²

Packaging Details: In bundles

Delivery Time: 7-15 days

Payment Terms: TT/LC

Supply Ability: 1000tons per month

Customization:

Galvanised Scaffold Tube - Customized Service

Brand Name: Bythai Scaffolding

Model Number: BT01

Place of Origin: China

Certification: SGS

Price: \$5-\$18

Packaging Details: In bundles

Delivery Time: 7-15 days

Payment Terms: TT/LC

Supply Ability: 1000tons per month

Weight: 6.4kg/m

Surface Treatment: Galvanised

Diameter: 48.3mm

Application: Scaffolding

Standard: EN39

Our Galvanised Scaffold Tube is made of high quality 3.2 thickness steel pipe and hot dip galvanized for added durability. It is stamped with our brand name, Bythai Scaffolding, as a mark of quality and authenticity.

We offer customized lengths to meet your specific needs, ensuring a perfect fit for your scaffolding projects. Our scaffold tube caps also provide added protection and safety.

With our strong and durable Galvanised Scaffold Tube, you can trust that your scaffolding structures will be safe and secure. Our tubes are compliant with the EN39 standard, guaranteeing quality and reliability.



Bythai Scaffolding Co.,Ltd



17300780862



info@bythaiscaffolding.com



bythaiscaff.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China