

## Stable Galvanised Scaffold Tube 6.4kg/m 3.2mm Thickness for Durable Scaffolding

Our Product Introduction

for more products please visit us on [bythaiscaff.com](http://bythaiscaff.com)

### Basic Information

- Place of Origin: China
- Brand Name: Bythai Scaffolding
- Certification: SGS
- Model Number: BT01
- Minimum Order Quantity: 1000
- Price: \$5-\$18
- Packaging Details: container
- Delivery Time: 10-15
- Payment Terms: TT/LC
- Supply Ability: 1000tons per month



### Product Specification

- Standard: EN39
- Application: Scaffolding
- Material: Galvanised Steel
- Diameter: 48.3mm
- Yield Strength: 245N/mm2
- Name: Galvanised Scaffold Tube
- Tensile Strength: 420N/mm2
- Thickness: 3.2mm
- Highlight: **Stable Galvanised Scaffold Tube,  
3.2mm Stable Galvanised Scaffold Tube,  
6.4kg/m Galvanized Scaffolding Tube**



**Product Description:**

Galvanised Scaffold Tube

The Galvanised Scaffold Tube is a high-quality, durable and versatile product that is essential for any scaffolding project. Made from seamless pipes, this scaffold tube is designed to provide maximum strength and stability while also being lightweight and easy to handle. With a thickness of 3.2mm and a diameter of 48.3mm, this scaffold tube is the perfect choice for a wide range of applications.

Product Attributes:

**Thickness:** 3.2mm

**Application:** Scaffolding

**Weight:** 6.4kg/m

**Standard:** EN39

**Diameter:** 48.3mm

The Galvanised Scaffold Tube is specifically designed for use in scaffolding applications. Its sturdy construction and high weight capacity make it ideal for supporting heavy loads and providing a stable platform for workers to perform their tasks. Whether you are working on a construction site, building maintenance, or any other scaffolding project, this tube is the perfect choice for your needs.

One of the key features of this scaffold tube is its galvanised coating. This coating provides excellent protection against corrosion, making the tube resistant to rust and other forms of damage. This ensures that the tube will last for years, even in harsh weather conditions or high-moisture environments.

The seamless pipes used in the production of this scaffold tube ensure a smooth and consistent surface, making it easier to erect and dismantle scaffolding structures. This also makes it safe for workers to handle, reducing the risk of injuries. Additionally, the seamless design provides a sleek and professional appearance, making it perfect for both indoor and outdoor use.

The Galvanised Scaffold Tube is also compatible with a wide range of scaffolding accessories, such as couplers, clamps, and connectors. This allows for easy customization and versatility in setting up scaffolding systems to suit your specific needs.

In addition to its functional benefits, this scaffold tube is also environmentally friendly. The galvanised coating not only protects the tube from corrosion, but it also reduces the need for frequent replacements, thus reducing waste and promoting sustainability.

Overall, the Galvanised Scaffold Tube is a reliable, durable, and high-quality product that is essential for any scaffolding project. Its advanced design, superior protection against corrosion, and compatibility with various accessories make it the top choice for professionals in the construction and maintenance industries.

**Features:**

Product Name: Galvanised Scaffold Tube

Yield Strength: 245N/mm2

Material: Galvanised Steel

Application: Scaffolding

Tensile Strength: 420N/mm2

Diameter: 48.3mm

Scaffold Tube

Scaffolding Tubes Galvanized

Tube and Coupler Scaffolding

**Technical Parameters:**

Product Name	Galvanised Scaffold Tube
Material	Galvanised Steel
Application	Scaffolding
Yield Strength	245N/mm2
Diameter	48.3mm
Weight	6.4kg/m
Tensile Strength	420N/mm2
Thickness	3.2mm
Standard	EN39
Surface Treatment	Galvanised
<b>Product Keywords</b>	<b>tube and coupler scaffolding, steel and pipe, galvanized scaffolding pipe tube</b>
Material	Galvanised Steel
Application	Scaffolding
Yield Strength	245N/mm2

Diameter	48.3mm
Weight	6.4kg/m
Tensile Strength	420N/mm <sup>2</sup>
Thickness	3.2mm
Standard	EN39
Surface Treatment	Galvanised

☰



**Bythai Scaffolding Co.,Ltd**



17300780862



info@bythaiscaffolding.com



bythaiscaff.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China