

## Steel Props, Galvanized Heavy-Duty Adjustable Telescopic Shoring Props, Multiple Sizes for Concrete Formwork Building Slab Construction Support

Our Product Introduction

for more products please visit us on [bythaiscaff.com](http://bythaiscaff.com)

### Basic Information

- Place of Origin: China
- Brand Name: Bythai
- Certification: SGS
- Model Number: SCA-FRAME-001
- Minimum Order Quantity: 1000
- Price: 4.5-9.8
- Packaging Details: container
- Delivery Time: 15-30 Working Days
- Payment Terms: L/C, T/T
- Supply Ability: 5000t/Month



### Product Specification

- Connection Type: Pin And Nut
- Adjustable Height: 1.6m-3.0m
- Thickness: 1.8mm, 2.0mm
- Application: Consturction,plants And Bridge
- Compatibility: Fits Standard Construction Scaffolding
- Height: Adjustable
- Loading Capacity: 20kN
- Size: 2200-4000mm Or Customized
- Threadtype: Acme Thread
- Color: Red/Blue/Green/Customized
- Function: Support
- Material: Steel
- Diameter: 48 Mm
- Length: 1.8~5.0m
- Standardcompliance: Meets EN 1065 And ASTM A500 Standards



### More Images





15084911343

[info@bythaiscaffolding.com](mailto:info@bythaiscaffolding.com)[bythaiscaff.com](http://bythaiscaff.com)

Room 702.TianMei Building,No.676 Shaoshan Road,Yuhua,Changsha, Hunan, China

## Product

### Description:

Our Heavy Duty Powder Coated Steel Commercial Construction Support Telescopic Prop Jack is designed for the most demanding construction projects. Featuring a robust steel construction with a durable powder-coated finish, this telescopic prop jack offers exceptional support and longevity. It provides adjustable height capabilities, making it versatile for various construction applications. The ease of use and reliability of this prop jack make it an essential tool for professionals seeking high-quality and dependable support solutions.

### Key Features:

**Durable:** The scaffolding steel prop tripod is made from high-quality steel, making it strong and long-lasting.

**Adjustable:** This product is designed to be adjustable, allowing for easy height adjustments to fit the needs of any construction project.

**Color:** The Adjustable Steel Prop comes in a sleek silver color, adding a professional and modern touch to any construction site.

#### Surface

**Treatment:** The steel prop is treated with hot-dip galvanization (HDG), ensuring it is rust-proof and can withstand harsh weather conditions.

**Weight:** With its heavy weight, this

product provides strong support and stability for scaffolding.

**Why Choose the Adjustable Steel Prop?**

When it comes to construction, having the right support is crucial for safety and efficiency. The Adjustable Steel Prop offers a reliable solution with its durable material and adjustable features. Its silver color and rust-proof surface treatment make it a practical and visually appealing choice for any construction project.

Applications:

**Support for scaffolding  
Construction projects  
Building maintenance and renovations  
Temporary structures**

Overall, the Adjustable Steel Prop is a versatile and essential tool for any construction site. Its durability, adjustability, and stability make it a reliable choice for all your scaffolding needs. With its sleek design and practical features, this product is a must-have for any construction project.

| LIGHT DUTY SHORING PROP |               |                 |                |                    |
|-------------------------|---------------|-----------------|----------------|--------------------|
| Min Height(m)           | Max Height(m) | Inner Tube (mm) | Outer Tube(mm) | Tube Thickness(mm) |
| 0.6                     | 1.1           | 40              | 48             | 1.4-2.5            |
| 0.8                     | 1.4           | 40              | 48             | 1.4-2.5            |
| 1.6                     | 2.9           | 40              | 48             | 1.4-2.5            |
| 1.8                     | 3.2           | 40              | 48             | 1.4-2.5            |
| 2.0                     | 3.6           | 40              | 48             | 1.4-2.5            |
| 2.2                     | 4.0           | 40              | 48             | 1.4-2.5            |

|                                                                                                                                                                                                                                                                                                                                                                        |               |                          |                 |                    |                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------|-----------------|--------------------|--------------------|
|                                                                                                                                                                                                                                                                                                                                                                        |               | MIDDLE DUTY SHORING PROP |                 |                    |                    |
| Min Height(m)                                                                                                                                                                                                                                                                                                                                                          |               | Max Height(m)            | Inner Tube (mm) | Outer Tube(mm)     | Tube Thickness(mm) |
| 1.8                                                                                                                                                                                                                                                                                                                                                                    |               | 3.2                      | 48              | 56                 | 1.8                |
| 2.0                                                                                                                                                                                                                                                                                                                                                                    |               | 3.5                      | 48              | 56                 | 1.8                |
| 2.0                                                                                                                                                                                                                                                                                                                                                                    |               | 3.6                      | 48              | 56                 | 1.8                |
| 2.2                                                                                                                                                                                                                                                                                                                                                                    |               | 4.0                      | 48              | 56                 | 2.0                |
|                                                                                                                                                                                                                                                                                                                                                                        |               |                          |                 |                    |                    |
|                                                                                                                                                                                                                                                                                                                                                                        |               | HEAVY DUTY SHORING PROP  |                 |                    |                    |
| Min Height(m)                                                                                                                                                                                                                                                                                                                                                          | Max Height(m) | Inner Tube (mm)          | Outer Tube(mm)  | Tube Thickness(mm) |                    |
| 1.6                                                                                                                                                                                                                                                                                                                                                                    | 2.9           | 48                       | 60              | 1.4-4.0            |                    |
| 1.8                                                                                                                                                                                                                                                                                                                                                                    | 3.2           | 48                       | 60              | 1.4-4.0            |                    |
| 2.0                                                                                                                                                                                                                                                                                                                                                                    | 3.5           | 48                       | 60              | 1.4-4.0            |                    |
| 2.0                                                                                                                                                                                                                                                                                                                                                                    | 3.6           | 48                       | 60              | 1.4-4.0            |                    |
| 2.2                                                                                                                                                                                                                                                                                                                                                                    | 4.0           | 48                       | 60              | 1.4-4.0            |                    |
| 3.0                                                                                                                                                                                                                                                                                                                                                                    | 5.0           | 48                       | 60              | 1.4-4.0            |                    |
| 3.5                                                                                                                                                                                                                                                                                                                                                                    | 6.0           | 48                       | 60              | 1.4-4.0            |                    |
| Applications:                                                                                                                                                                                                                                                                                                                                                          |               |                          |                 |                    |                    |
| Adjustable Steel Prop for Construction Site                                                                                                                                                                                                                                                                                                                            |               |                          |                 |                    |                    |
| Are you looking for a reliable and durable support for your construction site? Look no further than scaffolding steel prop tripod! Our adjustable steel prop is a must-have for any construction project. Made with high-quality steel and designed with stability and load bearing capacity in mind, our product is the perfect solution for your construction needs. |               |                          |                 |                    |                    |
| Brand Name: scaffolding steel prop                                                                                                                                                                                                                                                                                                                                     |               |                          |                 |                    |                    |
| Place of Origin: China Tianjin                                                                                                                                                                                                                                                                                                                                         |               |                          |                 |                    |                    |
| Minimum Order Quantity: 1000                                                                                                                                                                                                                                                                                                                                           |               |                          |                 |                    |                    |
| Price: \$4.5-\$8.5                                                                                                                                                                                                                                                                                                                                                     |               |                          |                 |                    |                    |
| Delivery Time: 10-25 days                                                                                                                                                                                                                                                                                                                                              |               |                          |                 |                    |                    |
| Size: Standard                                                                                                                                                                                                                                                                                                                                                         |               |                          |                 |                    |                    |
| Color: Silver                                                                                                                                                                                                                                                                                                                                                          |               |                          |                 |                    |                    |
| Height: Adjustable                                                                                                                                                                                                                                                                                                                                                     |               |                          |                 |                    |                    |

Our scaffolding steel prop tripod is made with high-quality steel and coated with a durable spray paint to ensure longevity and resistance to wear and tear. It is designed to provide maximum stability and support for all types of construction work. The adjustable feature of our steel prop makes it easy to use and perfect for various construction scenarios. Whether you need to support a wall, beam, or slab, our product can be easily adjusted to the desired height, providing the necessary support and ensuring the safety of workers and the structure. Our scaffolding steel prop tripod comes in a standard size, making it compatible with most construction equipment and materials. This eliminates the need for custom-made props, saving you time and money. In addition to its practicality and durability, our adjustable steel prop is also cost-effective. With its high load bearing capacity and long lifespan, you won't have to constantly replace or repair your support equipment, saving you money in the long run. So if you want a reliable, durable, and cost-effective support for your construction site, choose scaffolding steel prop tripod. Order now and experience the difference in your construction project!

## **Customizatio**

**n:**

Customized  
Service for  
Adjustable Steel  
Prop - scaffolding

steel prop

Brand Name:  
scaffolding steel  
prop

Place of Origin:  
China Tianjin

Minimum Order

Quantity: 1000

Price: 4.5-8.5

Delivery Time: 10-  
25

Feature: Durable  
Surface

Treatment: HDG

Color: Silver

Weight: Heavy

Material: Steel

At scaffolding steel

prop, we offer

customized

services for our

Adjustable Steel

Prop. Our steel

props for

construction are

designed to

provide reliable

building support

and are suitable

for a variety of

projects. We

understand that

each project is

unique and may

have different

requirements,

which is why we

offer a range of

customization

options to meet

your specific

needs.

Our minimum

order quantity for

customized

Adjustable Steel

Prop is 1000.

However, for

larger orders, we

can offer

competitive pricing

and discounts. Our

prices range from

4.5 to 8.5,

depending on the

customization

options chosen.

With our efficient

production process

and well-equipped

facilities, we can

deliver your order

within 10-25 days.

We understand the

importance of

timely delivery and

strive to meet all

deadlines.

Durability is a key

feature of our

Adjustable Steel

Prop. We use

high-quality steel

material and

employ advanced

techniques to

ensure that our

props can

withstand heavy

loads and harsh

construction

environments.

To ensure long-  
lasting protection,

our steel props are treated with Hot-Dip Galvanization (HDG). This surface treatment provides corrosion resistance and extends the lifespan of our props, making them suitable for both indoor and outdoor use. The standard color for our Adjustable Steel Prop is silver, which gives it a clean and professional look. However, we can also provide custom colors upon request. Our Adjustable Steel Prop is designed to be heavy-duty and can withstand heavy loads. This makes it an ideal choice for construction sites where strong and sturdy support is required. Our steel props are made from high-quality steel material, ensuring the strength and durability of our products. With our customized services, you can choose the specific type of steel material that best fits your project needs. In summary, our Adjustable Steel Prop is a versatile and durable building support system that can be customized to meet your specific requirements. Contact us now for more information and to place your customized order.

## **Packing and Shipping:**

Packaging and Shipping of Adjustable Steel Prop

Packaging:

The Adjustable Steel Prop will be packaged in a sturdy and secure manner to ensure safe delivery to our customers. Each prop will be wrapped in protective material and placed in a strong cardboard

box for shipping. The packaging will also include clear labeling to indicate the product name, quantity, and any special handling instructions.

#### Shipping:

We offer various shipping options for our Adjustable Steel Prop to cater to our customers' needs. The product can be shipped via air, sea, or land transportation. For international shipping, all necessary customs documents and paperwork will be prepared and included with the shipment to ensure a smooth delivery process. Our team works closely with trusted shipping partners to ensure timely and efficient delivery of our products to our customers worldwide.

